

## PCS24 SPLIT CORE CURRENT TRANSFORMER

### OVERVIEW

The PCS24 series are split-core current transformers. The CT can be mounted to existing panels, such as control centers or load centers, to measure or monitor wattage. These CTs can be mounted without removing existing cables for easier installation.



### APPLICATIONS

Energy and sub-metering products
Electrical load monitoring
Network equipment
Instruments and sensors
Control systems
Go GREEN initiatives

### FEATURES

0.94" window opening (ID)
Custom design Turns-Ratio available
Rigid housing case with UL 94V-0 durable plastic
PVC wire leads—22–16AWG
Approximate weight 180g

### SPECIFICATIONS

Standard Input Current 5-300A
Frequency 50Hz — 400Hz
Standard accuracy 0.5, 1, 3, 5
Insulation Voltage 4000 Vac/1min
Operating Temp. -40°C to +60°C
Storage Temp. -45°C to +85 °C

### ELECTRICAL SPECIFICATIONS

MODEL	INPUT CURRENT	AVAILABLE OUTPUT
PCS24-100	100 A	CURRENT OUTPUTS @ 20mA 33.3mA40mA 50mA100mA1A 5AVOLTAGE OUTPUTS @ 0.25V,0.333V, 0.5V,1V, 2V can be customized bycustomer)
PCS24-150	150 A	
PCS24-200	200 A	
PCS24-250	250 A	
PCS24-300	300 A	

