

PCOL13 SOLID CORE CURRENT TRANSFORMER

OVERVIEW

The PCOL13 series are UL listing mini-precision current transformers. The CT is small size and low cost.



ELECTRICAL SPECIFICATIONS

MODEL	INPUT CURRENT	AVAILABLE OUTPUT
PCOL13-10	10 A	OUTPUTS @ 5mA, 10mA, 15mA,20mA, 100mA,0.333V,0.5V,1V,2Vcan be customized by customer)
PCOL13-30	30 A	
PCOL13-50	50A	
PCOL13-80	80 A	
PCOL13-100	100 A	

APPLICATIONS

Energy and sub-metering products
Electrical load monitoring
Network equipment
Instruments and sensors
Control systems
Go GREEN initiatives

FEATURES

0.512" window opening (ID)
Custom design Turns-Ratio available
Rigid housing case with UL 94V-0 durable plastic
PVC wire leads—16~18AWG
UL Listing - UL 2808 / XOBA

SPECIFICATIONS

Standard Input Current : 0.01-100A
Frequency 50Hz — 400Hz
Standard accuracy 0.1,0.2,0.5
Insulation Voltage 3510 Vac/1min
Operating Temp. -40°C to +70°C
Storage Temp. -45°C to +85 °C

