

## PCO26 SOLID CORE CURRENT TRANSFORMER

### OVERVIEW

The PCO26 series are solid core energy monitoring current transformers. The CT is small size and low cost.



### APPLICATIONS

Energy and sub-metering products
Electrical load monitoring
Network equipment
Instruments and sensors
Control systems
Go GREEN initiatives

### FEATURES

1.024" window opening (ID)
Custom design Turns-Ratio available
Rigid housing case with UL 94V-0 durable plastic
PVC wire leads—16~18AWG
Approximate weight 200g

### SPECIFICATIONS

Standard Input Current 0.1-400A
Frequency 50Hz — 400Hz
Standard accuracy 0.1,0.2, 0.5,1,3
Insulation Voltage 4000 Vac/1min
Operating Temp. -40°C to +70°C
Storage Temp. -45°C to +85 °C

### ELECTRICAL SPECIFICATIONS

MODEL	INPUT CURRENT	AVAILABLE OUTPUT
PCO26-50	50 A	CURRENT OUTPUTS @ 40mA , 50mA,100mAVOLT-AGE OUTPUTS @ 0.25V,0.333V 0.5V, 1V, 2V (can be customized by customer)
PCO26-60	60 A	
PCO26-75	75 A	
PCO26-100	100 A	
PCO26-125	125 A	
PCO26-150	150 A	
PCO26-200	200 A	
PCO26-250	250 A	
PCO26-300	300 A	
PCO26-400	400 A	

