

PCH60 CURRENT TRANSFORMER

OVERVIEW

The PCH60 series current transformer is compact, smaller than other models with the current ratio of the transformer is small, clamshell-style terminal cover is well protected for the second terminal.



APPLICATIONS

Energy and sub-metering products
Electrical load monitoring
Network equipment
Instruments and sensors
Control systems
Go GREEN initiatives

FEATURES

21x61.5 window size
Custom design Turns-Ratio available
Rigid housing case with UL 94V-0 durable plastic
Output Terminal: M5 terminal
Approximate weight 500g

ADVANTAGE

Standard Input Current 0.5-1200A
Frequency 50Hz/60Hz
Standard accuracy 0.1,0.2,0.5,1,3
Insulation Voltage 4000 Vac/1min
Operating Temp. -40°C to +65°C
Storage Temp. -45°C to +85 °C

ELECTRICAL SPECIFICATIONS

MODEL	INPUT CURRENT	AVAILABLE OUTPUT
PCH60-300	300 A	CURRENT OUTPUTS @ 50mA, 100mA, 1A, 5AVoltage OUTPUTS @0.333V,0.5V,1V,2VOutput can be customized by customer
PCH60-400	400 A	
PCH60-500	500 A	
PCH60-600	600 A	
PCH60-800	800A	
PCH60-1000	1000A	
PCH60-1200	1200A	

